

PATTERN NAME: EUR-1 ASPERO

This pattern meets or exceeds all Type I requirements of CCC-W-408D and W-101.

| PRODUCT SPECIFICATIONS | |
|--|-----------------------------|
| Weight (Avg.): | 15 oz. (339 gr/m2) |
| Thickness: | N/A |
| Content: | Type I Vinyl |
| Width: | 52/54" (132/137 cm) |
| Backing: | Scrim |
| Installation: | Reverse Hang / Random Match |
| Custom colors, weights, widths and microventing are available. | |

| FIRE SAFETY/HAZARD CLASSIFICATION |
|---|
| <ul style="list-style-type: none"> • Euroclass EN13501 (B-s1,d0) • Meets BS476 Part 6/7-British Class 0 • Class A - ASTM E84 (GRC) |

| ENVIRONMENTAL & HEALTH |
|--|
| <ul style="list-style-type: none"> • Recyclable • Free of Phthalates, Formaldehyde, Heavy Metals (RoHS), PBDEs (Brominated Flame Retardants) • Prop 65 Compliant • Meets California Section 01350 Indoor Air Quality Standard (Low VOC) • Solvent-free Ink System |

| USGBC LEED SUPPORT | |
|------------------------------|--|
| Supports USGBC LEED | v4.1 Criteria |
| Materials and Resources | Building Product Disclosure and Optimization (Includes recycled content; construction waste management; HPDís) |
| Indoor Environmental Quality | Low emitting materials |

| PRODUCT USE ADVISORY |
|---|
| <p>This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make wallcovering cleanable and durable also render it low in permeability. Wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.</p> |

| WARRANTY |
|---|
| <p>All product is guaranteed to be free of defects in workmanship and material for five years. For additional details, visit our website at VersaDesignedSurfaces.com.</p> |