

**PATTERN NAME: INV15-2 LUNA**

This pattern meets or exceeds all Type I requirements of CCC-W-408D and W-101.

PRODUCT SPECIFICATIONS	
Weight (Avg.):	15 oz. (339 gr/m2)
Thickness:	N/A
Content:	Type I Vinyl
Width:	52/54" (132/137 cm)
Backing:	Scrim
Installation:	Reverse Hang / Random Match
Custom colors, weights, widths and microventing are available.	

FIRE SAFETY/HAZARD CLASSIFICATION
<ul style="list-style-type: none"> <li>• Class A - ASTM E84 (GRC)</li> <li>• Meets BS476 Part 6/7-British Class 0</li> <li>• GB8624-2012-B1(B-s2,d0,t0)</li> </ul>

ENVIRONMENTAL & HEALTH
<ul style="list-style-type: none"> <li>• Recyclable</li> <li>• Free of Phthalates, Formaldehyde, Heavy Metals (RoHS), PBDEs (Brominated Flame Retardants)</li> <li>• Prop 65 Compliant</li> <li>• Meets California Section 01350 Indoor Air Quality Standard (Low VOC)</li> <li>• Highly Cleanable Water-based Inks</li> <li>• Versa Permavent® Microventing Available</li> </ul>

USGBC LEED SUPPORT	
Supports USGBC LEED	v4.1 Criteria
Materials and Resources	Building Product Disclosure and Optimization (Includes recycled content; construction waste management; HPDIs)
Indoor Environmental Quality	Low emitting materials

PRODUCT USE ADVISORY
<p>This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make wallcovering cleanable and durable also render it low in permeability. Wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.</p>

WARRANTY
<p>All product is guaranteed to be free of defects in workmanship and material for five years. For additional details, visit our website at <a href="http://VersaDesignedSurfaces.com">VersaDesignedSurfaces.com</a>.</p>