

## GHIACCIAIO DGHC

This pattern meets or exceeds all Type II requirements of CCC-W-408D and W-101.

### PRODUCT SPECIFICATIONS

Weight (Avg.):	20 oz. (452 gr/m <sup>2</sup> )
Content:	Type II Vinyl
Width:	52/54" (132/137 cm), Trim to 50"
Total Mural Size:	4 Panel Set (200" w x 120" h)
Backing:	Osnaburg
Installation:	Non-Reverse Hang / Straight Across Match in Sequence
Custom colors, weights, widths and microventing are available.	

### FIRE SAFETY/HAZARD CLASSIFICATION

- Class A - ASTM E84 (GRC)
- Passes NFPA 286 Corner Burn
- NFPA 101 Life Safety Code
- BS476 Class 0
- CAN/ULC S102
- Euroclass EN13501 (B-s1,d0)

### ENVIRONMENTAL & HEALTH

- Health Product Declaration (HPD)
- Environmental Product Declaration (EPD)\*
- Recyclable
- Free of Phthalates, Formaldehyde, Heavy Metals (RoHS), PBDEs (Brominated Flame Retardants)
- Prop 65 Compliant
- Meets California Section 01350 Indoor Air Quality Standard (Low VOC)
- Aggressive Manufacturing Materials Recovery and Reuse Program
- Highly Cleanable Water-based Inks
- ASSURE Surface Protection Available
- Versa Permavent® Microventing Available

### USGBC LEED SUPPORT

Supports USGBC LEED	v4.1 Criteria
Materials and Resources	Building Product Disclosure and Optimization (Includes recycled content; construction waste management; HPDs)
Indoor Environmental Quality	Low emitting materials

### PRODUCT USE ADVISORY

This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make wallcovering cleanable and durable also render it low in permeability. Wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

### WARRANTY

All product is guaranteed to be free of defects in workmanship and material for five years. For additional details, visit our website at [VersaDesignedSurfaces.com](http://VersaDesignedSurfaces.com).